



AUTOMATIC VERTICAL FLAT CASE TRANSPORT SYSTEM

SERIES
925-TA/A KD
DATA SHEET

The Model 925-TA/A accommodates Ink Jet Coders or P/S Labelers to provide a Single or Dual Side Flat Corrugate Case Coding or Labeling System!



Shown without Automatic Case Accumulator

Features & General Specifications

- Automatically Destacks, Feeds & Restacks Flat Cases
- Case Sizes: Min.: 12" H x 16" L x 1/4"
Max.: 40"H x 44" L x 1"
- Baked Enamel Welded Steel Construction
- Adjustable Height Leveling Pads
- Works with most HSC & RSC Cases
- Touch Screen Controller for many adjustments
- Speeds up to 45 ppm depending upon case size
- Requires 220VAC/1 Ph and up to 80 psi @ 5 cfm
- Suitable for Coated and Non-Coated Stock
- Dimensions: 14' L x 3' W x 5' H (shipped in 3 Modules)
- Eliminates on-line delays caused by case coding changes
- Suitable for use with Ink Jet Coders or P/S
- Labelers for up to four-sided case identification



DALEMARK
INDUSTRIES, Inc.

575 Prospect St., #211
Lakewood, New Jersey 08701-5073
Tel: (732) 367-3100

fax: (732) 367-7031
e-mail: sales@dalemark.com
website: www.dalemark.com

Covered under one or more of the following PAT. Nos.:

3977317	3702000	734135
3081697	3808970	4068578
3964383	946271	4037529
1512180	3140376	261056



Printed in U.S.A.
© 2022 DALEMARK
Industries, Inc.

In U.S.A., Canada, U.K.