



# Hot Ink Rolls

## "10" Series

### Product Features

- Specialized foam roll that is friction loaded with Hot Melt Ink.
- Specifically formulated for use in Hot Ink Contact Printers.
- Excellent adhesion capabilities at low temperatures, this hot ink roll adheres to:
  - » Polyethylene
  - » Polypropylene
  - » Temperature sensitive substrates, cases and cartons
- Available in black, white, blue and special order colors.
- A medium setting product that performs best in the 200-270°F (93-132°C) temperature range.

### Significant Notes

For temperature ranges of 260-300°F (127-149°C), please test our 33 and 39 Series Hot Ink Rolls.

For temperature ranges of 260-325°F (127-163°C), please test our 30 Series Hot Ink Rolls.

This product does not contain any hazardous components required to be listed under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

No ACGIH or OSHA exposure guidelines have been established for any of the components in this product.

There are no anticipated conditions to avoid which may cause reactivity.

This product is incompatible with strong acids, bases and oxidizing agents.

This product is stable and hazardous polymerization will not occur.

Always consult the Material Safety Data Sheet for specific hazard information before using this product.

Contact sales support for any additional questions or comments.

### Use and Handling

To achieve maximum number of impressions from each roll, we recommend preheating the rollers at a temperature of 25°F (-3.88°C) degrees below the normal operating temperature.

The preheater should be used to warm the ink and not to overheat the roller.

The roller should be left in the printer with the heat on when use stops. If the printer/heater is turned off, the ink will be absorbed by the foam roller and will not release properly when reheated.

Dispose of this product in accordance with local, county, state and federal environmental regulations.

### Warranty

The shelf life for a Hot Ink Roller is one year from the date of manufacture. If rollers are stored properly in the original trays, normal usage has been confirmed for up to seven (7) years from the date of manufacture.



575 Prospect St., #211  
 Lakewood, New Jersey 08701-5073  
 Tel: (732) 367-3100

fax: (732) 367-7031  
 e-mail: sales@dalemark.com  
 website: www.dalemark.com

