



TABLETOP POP-TUBE LABELER

SERIES
7050-TT-PTL
DATA SHEET



The Series "PTL" Pop-Tube Labeler offers a semi-automatic labeling system for a full range of round and tapered tubes with 1/2" to 6" diameters and virtually any length without the need for costly attachments or modifications.

Features & General Specifications

- Solid state electronics
- Scrap rewind for quick start and removal of waste liner
- Photocell Label sensor
- Durable all steel frame with powder coat finish
- Footswitch activated
- Accepts most tapered products
- Product Size: 1/2" to 6"
- Minimum Label Size: 1/2" x 1/2"
- Maximum Label Width: 5"
- Maximum Roll Diameter: 12"
- Core Size Diameter: 3"
- Web Speed: 250" per min.

Physical Features & Optional Features

- Unit Dimensions: 17"W x 16"H x 34"L
- Shipping Weight: 75 pounds
- Electrical Requirements: 115 VAC, 60 Hz., Sgl
- Air Requirement: 60 PSI
- 7" Wide Label Kit
- Clear Label Photo Sensor
- Hot Stamp Imprinter
- Full Electric Operation; No air Required



DALEMARK
INDUSTRIES, Inc.

575 Prospect St., #211
Lakewood, New Jersey 08701-5073
Tel: (732) 367-3100

fax: (732) 367-7031
e-mail: sales@dalemark.com
website: www.dalemark.com



Covered under one or more of the following PAT. Nos.:

3977317	3702000	734135
3081697	3808970	4068578
3964383	946271	4037529
1512180	3140376	261056

Printed in U.S.A.
© 2023 DALEMARK
Industries, Inc.

In U.S.A., Canada, U.K.