

# A-POS MERCURY TABLETOP THERMAL TRANSFER CARE LABEL PRINTER



The industrial based Mercury Tabletop Thermal Transfer Printer is designed to provide 1 Side / 1 Color up to 2 Side/ 2 Color alphanumeric/logo copy onto poly and fabric based garment Care Labels in a compact & economical PC driven digital print System.

## MAIN FEATURES:

- **Easy to Change Thermal Ribbon and Tape -**

Just line them up with the back of the machine to set! Ribbon of all sizes can easily be changed without any tools.

- **Highly Economical Ribbon Saving Feature –**

Ribbon consumption is automatically economized providing a very cost effective in-house Care Label printing system.

- **Cuter -**

An optional Cold Cutter is available to allow automatic cut and re-stacking of your Care Label



# MERCURY SPECIFICATIONS

| Printer Specification                   | MERCURY 230  | MERCURY 430 II        | MERCURY 430 WL        | MERCURY 430 III       |
|---|--|-----------------------|-----------------------|-----------------------|
| Print Method                            | Thermal Transfer Printing  |                       |                       |                       |
| Printing Area                           | (W) 50mm x (L) 300mm   | (W) 100mm x (L) 300mm | (W) 100mm x (L) 300mm | (W) 100mm x (L) 300mm |
| Printing Resolution                     | 300dpi   |                       |                       |                       |
| Printing Speed                          | 4stepssetting: 80mm/sec, 100mm/sec, 120mm/sec, 150mm/se                                |                       |                       |                       |
| Max Print Width                         | 2"   | 4"                    | 4"                    | 4"                    |
| Character Font                          | All Windows Fonts  |                       |                       |                       |
| Barcode                                 | JANS · JAN13 · EANS · EAN13 · ITF · NW-7 · CODE39 · CODE93 · CODE128 · QR code · PDF41 |                       |                       |                       |
| Interface                               | Standard: USB, Serial (RS232C) & Parallel (Centronics)<br>Optional: LAN connector      |                       |                       |                       |
| SD Card Slot                            | Standard   |                       |                       |                       |
| CPU Relevant                            | Active clock: 200MHz   |                       |                       |                       |
| Memory                                  | 16MBytes   |                       |                       |                       |
| Adjustment Printhead Pressure           | Standards  |                       |                       |                       |
| Correcting function for Head Resistance | Equipped   |                       |                       |                       |
| Cutter                                  | Rotary cutter · Ultrasonic cutter  |                       |                       |                       |
| Adjustment for Ribbon Tension           | Automatic torque control   |                       |                       |                       |
| Display Printing Quality                | Addition method or deduction method switchable   |                       |                       |                       |
| Panel Display                           | Integrated Control Panel   |                       |                       |                       |
| Power Voltage                           | 1 00V-240V (50Hz/60Hz) Adapted to local voltage  |                       |                       |                       |
| Machine Size                            | (W)430mm x (D)440mm x (H) 680mm  |                       |                       |                       |
| Machine Weight                          | 48kg /12kg /25kg   |                       |                       |                       |
| Dual-Side Printing                      |  |                       | X                     | X                     |
| Dual Color Printing Pre-Side            |  | X                     |                       | X                     |



**DALEMARK**  
**INDUSTRIES, Inc.**

575 Prospect St., #211  
Lakewood, New Jersey 08701-5073  
Tel: (732) 367-3100

fax: (732) 367-7031  
e-mail: [sales@dalemark.com](mailto:sales@dalemark.com)  
website: [www.dalemark.com](http://www.dalemark.com)

Covered under one or more of the following PAT. Nos.:

|         |         |         |
|---------|---------|---------|
| 3977317 | 3702000 | 734135  |
| 3081697 | 3808970 | 4068578 |
| 3964383 | 946271  | 4037529 |
| 1512180 | 3140376 | 261056  |

Printed in U.S.A.  
© 2022 DALEMARK  
Industries, Inc.



In U.S.A., Canada, U.K.