

**The Model 925-TA/A accommodates Ink Jet Coders or P/S Labelers to provide a
Single or Dual Side Flat Corrugate Case Coding or Labeling System!**



Shown without Automatic Case Accumulator

Features & General Specifications

- | | |
|--|--|
| <ul style="list-style-type: none"> • Automatically Destacks, Feeds & Restacks Flat Cases • Case Sizes: Min.: 12" L x 13.7" H x 3/16" Thick
Max.: 24.25" L x 23.5" H x 3/14" Thick • Powder Coated Welded Steel Construction • Adjustable Height Leveling Pads • Works with flat RSC Cases • Touch Screen Controller for most adjustments – Speed, On/Off & Stop • Speeds up to 40 ppm depending upon case size • E Stop included | <ul style="list-style-type: none"> • Requires 220VAC/1 Ph and up to 80 psi @ 5 cfm • Suitable for Coated and Non-Coated Stock • Dimensions: 9' L x 4' W x 5' H (not including Opt. Accumulator) • Eliminates on-line delays caused by case coding changes • Larger Case Sides by request • Suitable for integration with most C.I.J., T.I.J. & D.O.D. Ink Jet Coders and any P/S Applicator • Very Low Maintenance needed |
|--|--|



**DALEMARK
INDUSTRIES, Inc.**

575 Prospect St., #211
Lakewood, New Jersey 08701-5073
Tel: (732) 367-3100

fax: (732) 367-7031
e-mail: sales@dalemark.com
website: www.dalemark.com



Covered under one or more of the following PAT. Nos.:

3977317	3702000	734135
3081697	3808970	4068578
3964383	946271	4037529
1512180	3140376	261056

Printed in U.S.A.
© 2024 DALEMARK
Industries, Inc.

In U.S.A.. Canada. U.K.