

## High Resolution Handheld Ink Jet Coder



**Ergonomically Designed**  
For comfortable use



**Variable Throw Distance Supported**  
Different sliding wheel sizes for available  
DPI



**Batteries**  
Two Rechargeable High Performance  
Batteries are in standard package.  
4-6 Hours of continuous printing.



**Flight Box:**  
The Flight Box is standard packaging  
for printer and accessories



**Instant Printing**  
Prints up to 12mm high copy  
anywhere and anytime

# Features

## Selectable Languages:

Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian.

## Fonts:

Default Font is Arial

## Barcodes:

UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, ENA128, PDF417, DATAMATRIX, QR

## Counters:

Flexible setting for Serial Number & Lot Codes

## Multi Management:

Multi-level password protection (Operator, Technician & Administrator)

## Date Format:

Variety of Date Modes available ( Production, Effective Date, Expiration Date, etc.)



# Technical Parameters

## Technology:

Utilizes HP Driver Board

## Dimensions:

143.5H x 123W x 236D mm / 5.65"H x 4.84"W x 9.3"D

## Power Supply:

AC 90V-240V / 50-60HZ, 60W

## Automatically Adjusts Throw Distance:

Two deflectors available for different products

## Throw Distance:

Adjustable: 1.5mm/2.5mm/5mm Sliding wheel available

## Prints:

Barcodes, Character, Alpha-Numeric, Logos, Date/Time, Expiration Date, Shift Codes, etc.

## Print Resolution:

300 DPI

## Port:

USB 2.0: Support U-Disk

## Interface:

5 inch 800 x 480 Color LCD Touch Screen

## Battery:

Side or Downward printing are Standard  
Standard (2) Rechargeable High Capacity Batteries  
Capacity: (3) 2200mAh Battery Module  
Voltage: 11.1V--12.6V  
Lifetime: >300 cycle number  
Stand-by Time: >8H  
Print time: >4H

## Ink Management:

Automatically recognizes ink types and identifies the Optimum printing parameters  
Automatic measuring system of usage of the ink

## Ink Feed:

Support HP TIJ2.5 42ML Ink Cartridges

## Product Certification:

CE, FCC  
50 ~ 600 DPI

## Environment:

Working Environment: -10° - +55°C; 10% - 85%RH  
Storage Environment: -25° - +80°C; 10% - 90%RH



DALEMARK  
INDUSTRIES, Inc.

575 Prospect St., #211

Lakewood, New Jersey 08701-5073

Tel: (732) 367-3100

fax: (732) 367-7031

e-mail: [sales@dalemark.com](mailto:sales@dalemark.com)

website: [www.dalemark.com](http://www.dalemark.com)

