



MODEL 830 “FBGT” FLOOR BASE GAP TRANSPORT

SERIES
830-FBGT
DATA SHEET

Our Model “FBGT” Floor Based Gap Transport is designed to be easily placed into your production line to provide a simple and affordable way to transfer round, oval and rectangular containers from one conveyor to the next or where product spacing is needed for ink jet coding or laser bottom coding.



Standard Features

- American Made
- Stainless Steel & Anodized Aluminum Frame
- Speeds up to 80 fpm
- Pinch Point Protection
- Variable Speed Drive.
- Locking Castors/Adj. Floor Pads
- Optional Bottom Slide
- I/J Print Head Mounting Bracket
- Optional 2” High Transport Belt

Specifications

- Dual Brother AC Motors
- Operates on 115 VAC
- Independent Adj. Belt Opening 0” to 12”
- Uses 12” x 1” Non-Scuffing Transport Belts
- Gripper Belts
- 6” Adj. Belt Height



**DALEMARK
INDUSTRIES, Inc.**

575 Prospect St., #211
Lakewood, New Jersey 08701-5073
Tel: (732) 367-3100

fax: (732) 367-7031
e-mail: sales@dalemark.com
website: www.dalemark.com



Covered under one or more of the following PAT. Nos.:

3977317	3702000	734135
3081697	3808970	4068578
3964383	946271	4037529
1512180	3140376	261056

Printed in U.S.A.
© 2022 DALEMARK
Industries, Inc.

In U.S.A.. Canada. U.K.